

Industrial cooling systems RKV series



# DAIKIN Fluid Technology GmbH

## Partner of the industry for over 55 years

DAIKIN Fluid Technology GmbH combines the technological heritage and more than 55 years of experience of DELTATHERM®, founded in 1971 in Much, Germany, with the global expertise of the DAIKIN Group. Since 2026, the company has entered a new era as part of Daikin Industries, offering industrial cooling and temperature control solutions that unite maximum efficiency, reliability, and sustainability.

Since its foundation, the company has been supplying a wide range of industries – including machine tool manufacturing, laser technology, chemical and food processing industries, and environmental testing – with high-quality and durable cooling systems. The high level of vertical integration and flexibility in customer-specific design developed by DELTATHERM® are now complemented by advanced control technology, energy-efficient solutions, and the global quality standards of the DAIKIN Group.

The portfolio includes industrial chillers, heat exchanger systems, process temperature control units, heating systems, and a variety of cooling components. From standard units to customized special solutions, systems are developed that are optimally tailored to customers' individual production processes. A nearly complete in-house manufacturing depth – from engineering and software development to control cabinet construction, assembly, painting, and comprehensive functional testing – ensures the highest quality standards and fast response times. All core components are sourced exclusively from globally renowned manufacturers to guarantee maximum reliability.

With the commitment “High Quality, High Efficiency, High Reliability,” DAIKIN Fluid Technology GmbH develops solutions that ensure maximum temperature stability, safeguard production processes, and at the same time support the transition toward a sustainable industrial future. The company combines technological strength with global competence, creating a new generation of industrial cooling and temperature control systems together with its customers.

In the field of after-sales service, DAIKIN Fluid Technology GmbH provides reliable, globally supported customer service. In addition to the long-established international DELTATHERM service network spanning more than 60 countries, customers now benefit from the expanded service infrastructure of the DAIKIN Group.

This includes:

- Global plant service
- Service hotline to our experts, in German and English
- All standard components in stock and available globally in the shortest time by express mail
- Replacement part availability > 95 %
- An expanding worldwide network of service partners with locations on 6 continents – in Europe, North America, South America, Africa, Asia and Australia
- Online service, through which we can check and maintain your systems
- Ensuring the productivity of your DAIKIN - DELTATHERM® machines



# RKV series

## Compact cooling units and cooling systems for medium capacities

This model series was developed on the basis of comprehensive research and many years of practical experience by **DAIKIN - DELTATHERM®** and further improved upon. Through a series of measures cooling capacity, efficiency and operational reliability were further improved and in this way a trend-setting cold water heat exchanger generation was designed.

The **DAIKIN - DELTATHERM®** industrial cooling systems of the RKV series consist of the following components: cold water circuit, water circuit and electrical technology, completely fitted in one housing. The cooling of the circulation medium (normally water, optionally also antifreeze, oil or deionised water) is carried out by a heat exchanger, which is known as the evaporator.

The **DAIKIN - DELTATHERM®** industrial coolers, which are ready for connection and have been tested by our in-house performance testing equipment are already completely equipped in the basic version. For customer-specific requirements a comprehensive option package is available, with which we are able to fulfil all of our customers' technically feasible wishes.

The devices are designed for indoor installation as standard and can also be optionally designed for outdoor installation.

## The functional principle

### The refrigeration cycle

The refrigerant cycle consists of a compressor, air-cooled condenser, expansion valve and evaporator. Various equipment options are available depending on the process requirements. Only modern refrigerants with low global warming potential, such as R454C, are used. All refrigeration components are sourced from brand-name manufacturers and are designed for high operational reliability, long service life and worldwide availability. The entire refrigeration cycle is designed for efficient, economical and sustainable operation and meets the applicable requirements of the CE directives and DIN EN 378.

### The electronics circuit

All electrical equipment is designed for safe and reliable operation of the industrial cooling system and complies with current standards. Precise temperature control is achieved in all models of the RKV series via a microprocessor-controlled digital temperature controller.

### The water circuit

The water circuit is fully integrated into the sturdy industrial housing and is made of corrosion-resistant materials as standard (depending on the medium). The water tank is made of highly stable, water-neutral plastic and is equipped with a tank cover ; a stainless steel version is available as an option.

The hydraulic decoupling of the water and refrigerant circuits opens up an extremely wide range of applications. The water circuit is completely pre-assembled and its design – consisting of piping, evaporator and pumps – is tailored to a defined volume flow and operating pressure. Pumps for higher pressures and/or larger volume flows are available for special requirements. In addition, alternative circulation media such as oil can be used. A continuous flow cooler version is also available as an option, either without a tank or without a pump.

### Short specification of the standard equipment

- Compact device tested by us in-house, in test run lasting several hours
- Compact interior housing for inside installation
- Device standing on wheels (RKV 1.6 - RKV 10.6)
- Device standing on tracks (RKV 11.6 - RKV 16.6)
- Painted in RAL 7012
- Air-cooled condenser with microchannel technology
- Axial fan, extremely quiet and maintenance-free, with touch protection; with EC technology depending on performance class
- CFC-free refrigerants with low global warming potential
- Hermetic compressor, 100% suction-gas cooled
- Evaporator as plate heat exchanger
- Expansion device for optimum refrigerant injection
- Intrinsically safe refrigeration circuit
- Air filter mat
- Pump bypass valve for system protection
- Manual medium filling via filler neck
- Visual medium level indicator
- Medium circuit piping made of corrosion-inhibiting materials (depending on medium)
- Medium container made of plastic, thermally insulated
- Stainless steel pump
- Digital temperature controller with setpoint and actual value display
- Switching and control elements fully wired
- External on/off switch
- Potential-free collective fault signal
- Medium temperature adjustable from +8 °C to + 25 °C
- Operating range from +8 °C to +42 °C ambient temperature
- Tank emptying

**Available options**

- Outdoor installation
- Fans with air duct connection
- Split design
- Water-cooled condenser
- Noise-reduced design
- Refrigeration pressure gauge for high and low pressure sides
- Medium temperature < + 8 °C
- Medium temperature up to 40 °C
- Increased temperature stability ± 0.5 K/ 0.1 K/ 0.02 K
- Multi-circuit system
- Heat recovery
- Fixed bypass
- Pump pressure gauge
- Flow monitor with analogue or digital signal
- Medium filter
- Shut-off valve in flow and return
- Automatic tank filling via mechanical float switch
- Automatic tank filling via solenoid valve
- Tank heating for temperature control
- Check valve and solenoid valve for the water circuit (consumer higher than cooler)
- Reinforced pump
- Water circuit made of stainless steel or PVC for deionised water
- Conductivity monitoring
- Air filter mat monitoring
- Stepless speed control of the fans
- Wire target marking
- Heavy-duty connectors (e.g. Harting)
- 24 VDC control voltage
- Special voltages and frequencies (50/60 Hz)
- Limit temperature monitoring
- Reference temperature control
- External temperature sensor
- Control cabinet heating
- Control cabinet fan
- Bus connection, e.g. Profibus DP / Ethernet / Profinet / Modbus TCP
- Individual fault indicators (in plain text display or as bit technology)
- RAL special colour of your choice
- Level monitoring with signal contact and/or optical signalling
- Installation feet

Series Type RKV		1.6	2.6	3.6	4.6	5.6	6.6	7.6	8.6	9.6	10.6	11.6	12.6	13.6	14.6	15.6	16.6		
Cooling performance at water inflow	kW																		
+10 °C		6,3	7,4	9,4	10,6	13,3	15,7	19,9	26,0	31,3	35,5	38,5	43,0	52,0	62,6	77,0	93,9		
+15 °C		7,8	9,0	11,2	12,8	15,9	18,9	23,9	31,0	37,0	42,0	46,0	52,0	60,0	74,0	92,0	110,0		
+20 °C		9,1	10,7	13,3	15,3	18,8	22,5	28,4	36,8	44,3	47,5	54,5	61,0	73,6	88,6	109,0	132,9		
Compressor drive	kW	1,8	2,0	2,5	2,8	3,5	4,1	5,3	7,5	8,8	11,1	11,1	12,8	2x 7,5	2x 8,7	2x 11,1	3x 8,7		
Air capacity	m³/h	4500					12000					24000			36000				
Number of fans		1					1					2			3				
Pump capacity	m³/h	1,2	1,5	1,8	2,2	2,7	3,66	4,56	5,1	6,0	6,8	7,8	8,6	10,3	12,2	13,8	15,7		
Pump drive	kW	1,3					2,2			3,0		3,0		4,0		4,0			
Pump pressure	bar	4,0	3,9	3,6	3,4	3,1	3,8	3,4	3,0	2,8	2,4	3,3	3,0	5,3	5,0	4,5	4,2		
Connected load	kW	5,1	5,1	5,7	6,0	6,9	7,5	8,7	10,9	14,0	16,4	16,6	18,3	21,4	24,1	30,0	33,9		
max. connected load*	kW	5,5	5,5	6,4	7,0	8,1	9,7	11,7	15,4	18,5	21,8	23,1	26,1	30,5	35,0	43,0	50,5		
electr. connection**	Hz	400 V / 50 Hz 460 V / 60 Hz					400 V / 50 Hz												
Tank contents	l	60					150					200							
Water connections	Zoll IG	1					1 1/2					1 1/2			2				
Dimensions about																			
Width	mm	600					750					750			750				
Length	mm	600					750					1500			2250				
Height	mm	1980					2040					2050			2050				
Empty weight about	kg	180	180	190	200	210	315	325	350	390	480	580	590	610	630	820	860		

\* at 15°C medium and 32° ambient temperature / \*\* other voltages and frequencies on request

Water temperature range: from +10 °C to +25 °C (other ranges on request)

Type of cooling: Air-cooled with axial fan (water-cooled or with air duct connection on request)

Designed ambient temperature: +32 °C (higher and lower temperatures on request)

Range of application of the industrial cooler: + 8 °C to + 42 °C ambient temperature (higher and lower temperatures on request)

Circulation medium: drinking water (according to specification) with a spread of about 5K between water inlet and outlet (other ranges on request)

## DAIKIN Fluid Technology GmbH

Gewerbegebiet Bövingen 122 · 53804 Much · Germany  
Phone +49 (0) 2245 6107-0 · info@daikin-fluidtechnology.de

## Further products from our product range



Industrial series cooling towers with open or closed circuits from 80 to 18,000 kW cooling capacity



Dry and hybrid coolers for water, oil or emulsion from 0.5 to 15,000 kW cooling capacity



Rack chillers in the power range from 0.15 to 3 kW cooling capacity; as heat exchanger up to 10 kW



Industrial cooling machines for water, oil and emulsion from 0.2 to 5,000 kW cooling capacity



Temperature control systems for water up to 160 °C and oil up to 350 °C



Immersion chillers for water, oil and emulsion from 1.7 to 115 kW cooling capacity

